

AMISEAL FIX

High concentrate and durable fibre fixation and wetting agent for asbestos containing surfaces.

DESCRIPTION

AMISEAL FIX is a waterborn fibre fixation agent composed of a dispersion of micro-polymer and additives derived from nanotechnology, specially formulated to fix asbestos fibres, as wetting agent and with high penetration based on low surface tension with the goal to impregnate and consolidate asbestos containing surfaces and fix asbestos fibres.

AMISEAL FIX is used on:

- » Roof plates and insulation materials
- » Plasters, (old)paints and coatings.
- » Other asbestos containing materials.

ADVANTAGES

- » Stops the spreading of asbestos fibres.
- » Fast and efficient application.
- » Impregnation in depth, depending the type of surface.
- » For inside and outside use.
- » VOC and solvent free.

APPLICATION
PREPARATION OF THE SURFACE

- » Remove standing water; apply on a dry surface only.
- » Temperature during application and drying: 5 – 35°C.
- » Shake before use. Do not dilute.

APPLICATION AND FINISH

- » Spray apply under low pressure or alternative with roller or paintbrush.
- » Consumption: up to 10m²/litre, depending surface porosity. Apply until saturation. In case of high porous surfaces, apply in two passes.
- » To ensure durable encapsulation of asbestos containing surfaces and building parts, apply AMISEAL COAT encapsulation coating after AMISEAL FIX has cured.

Local rules regarding asbestos removal or encapsulation to be respected.

CARACTERISTICS

Density(ind.)	1 kg/litre
Colour	Blue
Consumption	Depending surface; up to 10m ² /litre
Surface tension	15-20 dyne/cm
Adhesion to concrete	> 0,5 N/mm ² (ISO4624)
Temperature resistance after drying	-20°C to +80°C.
Drying time	1 to 12h, depending consumption and conditions.

PACKAGING

- » 5 litre; pallet: 128 x 5 litre.
- » 1 litre with sprayhead.

STORAGE

Store dry at + 5 ° C to + 20 ° C. Use before: 12 months from manufacture (original unopened packaging).

SAFETY

Consult safety data sheet prior to use.

DATE OF THIS EDITION: 24/01/2019

Our general conditions of sale apply. This document does not have a contractual value. This technical data sheet replaces and annuls the previous edition. The information given in this sheet has the purpose to inform and advice you. Hevadex bvba reserve the right to amend or change this information without notice. All information is given in good faith and without any warranty. The application, use and processing of these products are beyond our control and therefore the entire responsibility of the user/client/applicator. The user of the product must test the product's suitability and apply for the intended purpose. Established liability if any for any reason is always limited to the value of the goods supplied by HEVADEX bvba. The products and systems are manufactured under total quality management. HEVADEX bvba reserves the right to change the properties of its products. Users must always refer to the most recent issue of the local Product Data Sheet, copies of which will be supplied on request.